

Tuesday Booths Specs







Colors



EXTERIOR: ELECTROSTATIC COATED

STANDARD

Cloud Storm Hazel Mint Sountsea Taffy

INTERIOR	CARPET	SEAT	HANDLE
 Acoustic PET Panel Hazel	 Standard Dark Grey Felt FP1-1	 Acoustic PET Panel Hazel	 Ash Wood

Features

 QUICK ASSEMBLY	 PLUG-&-PLAY TECHNOLOGY	 DOUBLE LAMINATED GLASS (6+1+4)MM	 DAYLIGHT LED LIGHTNING	 INTEGRATED VENTILATION
 MAGNETIC DOOR SYSTEM	 ALUMINIUM FRAMED DOOR	 INTERNAL SWITCHES & SENSORS	 OPTIONAL MOVING KIT	 ABILITY TO PORT FIRE SERVICES

Tuesday Bureau Booth



Capacity	1 Person
Internal Dimensions (mm)	1000w x 800d x 2000h
External Dimensions (mm)	1100w x 900d x 2100h
Glass Panels	Double laminated (6mm + 1mm + 4mm)
Door	1800h x 80d x 11w
Furniture Options	x1 upholstered bench seats with back & central laminated table
GPO USB Data	Wall-mounted: UL/CE 220-240v power socket, 2x USB, 1x USB-C.
Lighting	4000k (150Lx) Daylight LED lighting
Ventilation & Airflow	78 m3/hr. Refreshing air every two minutes guaranteeing excellent oxygen rates.
Lighting & Ventilation Operation	Motion sensor with variable speed fan control
Power Supply	100-240V/50-60Hz power supply
Weight	224kg (Pod+Furniture)
Acoustic Treatment	Leading the Sound Pod Industry STC 30 dB & RT0.25s NIC=25dB D/C50, 0.76 STI A+

Tuesday+ Bureau Booth



Capacity	1-4 Person
Internal Dimensions (mm)	2100w x 1100d x 2100h
External Dimensions (mm)	2200w x 1220d x 2100h
Glass Panels	Double laminated (6mm + 1mm + 4mm)
Door	1800h x 80d x 11w
Furniture Options	x2 upholstered bench seats with back & central laminated table
GPO USB Data	Wall-mounted: UL/CE 220-240v power socket, 2x USB, 1x USB-C.
Lighting	3500k Dimmable Strip lights + Additional spotlight
Ventilation & Airflow	78 m3/hr. Refreshing air every two minutes guaranteeing excellent oxygen rates.
Lighting & Ventilation Operation	Motion sensor with variable speed fan control
Power Supply	100-240V/50-60Hz power supply
Acoustic Treatment	Leading the Sound Pod Industry STC 30 dB & RT0.25s NIC=25dB D/C50, 0.76 STI A+

Capability, Certifications & Important Info

We manufacture each component of our booths in state-of-the-art facilities across Australia and Asia, lead by our team of design experts and product managers.

Our global manufacturing operation enables us to deliver large-scale projects to our worldwide client base within competitive time frames.

Importantly, the end-to-end management of our supply chain guarantees a high quality product with premium customer experience from purchase, to delivery to post-install service.

Two large-scale production facilities



On-site acoustic and quality testing teams



Fully certified environmental and quality product line



Global network of local installation and assembly partners



Team of highly trained local customer service providers.



Two year structural warranty



Standard lead-time of 3-4 weeks for metro deliveries (custom options up to 10 weeks)



Limited local stock in various sizes and colours available for delivery within 1-2 weeks.

Our Certifications

- Accessible options
- PET Fire Tested
- ISO: 9001-2015 Quality Certified
- ISO: 14001-2015 Environmental Certified
- FSC Certified
- AS/NZS 2208: 1996 Certified Glass
- UL and CE Certified
- Class B Certified Panels
Fire Growth Rate Index 153.2
- ASTM E84-19A Tested
Flame Spread Index 15
Smoke Development Index 185

